

ST★RTRAC

26

MID ROPS



Powered by
MITSUBISHI
DIESEL ENGINE

www.startractors.com

STAGE V

STARTRAC 26

EU HOMOLOGATED TRACTOR MODEL

STAGE V

Your **STAR** Performer

STYLE
COMFORT
VERSATILITY

ENGINE

Engine Horse Power Ps (kW)	25 (18.2)
Engine Type	Mitsubishi MVS3L2 - Stage - V
No. of Cylinder	3
Capacity (CC)	1319
Rated Speed (RPM)	2500
Cooling System	Liquid Cooled
Bore / Stroke (mm)	78/92
Max Torque (Nm) @ RPM	76.3 (Nm) @ 2000 RPM

TRANSMISSION

Type	Sliding Mesh Transmission : Side Shift Gear Levers
Gears	9 Forward, 3 Reverse
PTO RPM	540 & 540 E
Steering	Hydrostatic Power Steering
Brake Type	Multi Disc Oil Immersed

HYDRAULIC

Hydraulic System	Auto Draft Sensing & Depth Control (2 Levers)
Lift Capacity (kgs.)	850 (at Lower Link Point)
No. of Pumps	2 (One for Hydrostatic Steering & Other for Hydraulic System)
Auxiliary Hydraulics	1 DA Auxiliary Hydraulics with 2 QRCs

MID ROPS



Next Generation Styling



Hydrostatic Power Steering



Engine : Stage V Mitsubishi 3 Cylinder



9+3 Gears Side Shift Levers



Front Opening Bonnet



Differential Lock



Ergonomic Seating & Footboard Area



Powerful 850 kg Hyd. Lifting Capacity



Powered by
MITSUBISHI DIESEL ENGINE



Agriculture



Turf



Industrial (Flotation)



Agricultural Wide Plus



Agrimax Turf RT 333 Garden



Wider F - Agri



Industrial (Regular)



Basic Agri

TYRE OPTIONS

Front	180/85D12	23 x 8.5 - 12	23 x 8.5 - 12	180/85D12	240/60R12	23 x 8.5 - 12	23 x 8.5 - 12	5.00 x 12
Rear	8.30 x 20	33 x 15.5 - 16.5	33 x 15.5 - 16.5	280/70R20	320/65R18	280/70R18	12 x 16.5	8.00 x 18

SPEED & DIMENSIONS#

Max. Speed Rounded Off (km/hr)	20	18	19	20	19	18	19	18
Size L x W x H (mm)	2700* x 1080 x 2190	2700* x 1390 x 2140	2700* x 1390 x 2140	2700* x 1167 x 2185	2700* x 1220 x 2170	2700* x 1220 x 2150	2700* x 1264 x 2140	2700* x 1050 x 2150
Wheel Base (mm)	1490	1490	1490	1490	1490	1490	1490	1490
Rear Track Center (mm)	811 to 988	980 to 1080	980 to 1080	883	883 to 988	845 to 988	939	743 to 988
Weight (kg)	1008	1050	1078	1039	1039	1014	1052	987

*Dimensions are with Standard Lower Links, it may vary with longer linkages.

#+/- 5% Tolerance variations

Note : Products undergo continuous upgradations. Hence, above mentioned specifications are subject to change without prior notice.