

STARTRAC

2614

MID ROPS



Powered by
MITSUBISHI
DIESEL ENGINE

www.startractors.com

STAGE V

STARTRAC 2614

Tractor with Hydrostatic Transmission

STAGE V

Your **STAR** Performer

STYLE
COMFORT
VERSATILITY

ENGINE

Engine Horse Power Ps (kW)	25 (18.2)
Engine Type	Mitsubishi MVS3L2 - Stage - V : Naturally Aspirated
No. of Cylinder	3
Capacity (CC)	1319
Rated Speed (RPM)	2500
Cooling System	Liquid Cooled
Bore / Stroke (mm)	78/92
Max Torque (Nm) @ RPM	76.3 (Nm) @ 2000 RPM

TRANSMISSION

Type	Hydrostatic
Gears	3 Forward / 3 Reverse, Options : Low, Medium or High Gear
PTO RPM	Rear 540 / Mid 2000
Steering	Hydrostatic Power Steering
Brake Type	Multi Disc Oil Immersed


HYDRAULIC

Hydraulic System	Precision Control
Lift Capacity (kgs.)	900 (at Lower Link Point)
No. of Pumps	2 (Total 28 LPM)
Auxiliary Hydraulics	1 DA Auxiliary Hydraulics with 2 QRCs

MID ROPS



Next Generation Styling



Hydrostatic Power Steering



Engine : Stage V Mitsubishi 3 Cylinder



Twin HST Pedals for Easy & Quick - FWD. & REV.



2 PTO : Rear & Mid.



Differential Lock



Ergonomic Seating & Full Flat Footboard Area



Powerful 900 kg Hyd. Lifting Capacity



TYRE OPTIONS

	Agriculture	Turf	Industrial (Flotation)	Agricultural Wide Plus	Agrimax Turf RT 333 Garden	Wider F - Agri	Industrial (Regular)	Basic Agri
Front	180/85D12	23 x 8.5 - 12	23 x 8.5 - 12	180/85D12	240/60R12	23 x 8.5 - 12	23 x 8.5 - 12	5.00 x 12
Rear	8.30 x 20	33 x 15.5 - 16.5	33 x 15.5 - 16.5	280/70R20	320/65R18	280/70R18	12 x 16.5	8.00 x 18

SPEED & DIMENSIONS*

	Agriculture	Turf	Industrial (Flotation)	Agricultural Wide Plus	Agrimax Turf RT 333 Garden	Wider F - Agri	Industrial (Regular)	Basic Agri
Max. Speed Rounded Off (km/hr)	0 to 22	0 to 21	0 to 21	0 to 22	0 to 21	0 to 21	0 to 21	0 to 20
Size L x W x H (mm)	2769 x 1140 x 2137	2769 x 1470 x 2129	2769 x 1485 x 2113	2769 x 1169 x 2137	2769 x 1199 x 2128	2769 x 1162 x 2154	2769 x 1271 x 2113	2769 x 1140 x 2100
Wheel Base (mm)	1550	1550	1550	1550	1550	1550	1550	1550
Rear Track Center (mm)	811 to 988	980 to 1080	980 to 1080	883	951 to 988	883 to 988	939	811 to 988
Weight (kg)	1093	1135	1163	1125	1125	1099	1137	1072

*+/- 5% Tolerance variations

Note : Products undergo continuous upgrades, Hence, above mentioned specifications are subject to change without prior notice.